



Seed VMF 3000/H, M, S6H

Automatic 3 hands

Our automatic movement is equipped with a double barrel and a variable inertia balance, giving the movements better operating stability and optimal timing. With its small dimensions rarely found on the market, it offers extremely wide scope for creativity.

Fitting diameter	23.3 mm (10 1/2")
Depth	3.9 mm
Indications and functions	Hour, minute, seconds sub-dial at 6h
Type of balance	Variable inertia with gold inertia-blocks
Frequency	4 Hz (28,800 A/h)
Type of stud holder	Mobile
Type of balance-spring	Flat
Type of oscillating weight	Tungsten
Oscillating weight winding direction	Single direction in clockwise sense of the weight viewing from the dial side
Power-reserve	50 hours
Chronometry	Double-barrel rapid rotation in series Variable inertia balance
Number of components	189
Number of jewels	28
Specific features and finishes	<ul style="list-style-type: none"> • Circular-grained plate on dial side and bridge side • Motion-work bridge, circular-grained, dial side • Bridges with Côtes de Genève decor, rhodium-plated, bicolour engraving • Bevels, counterbores and apertures diamond-polished • Ceramic ball-bearing • Pivots and flanges rolled • Wheels circular-grained on 2 faces • Flat-head screws, locked • Bridges hand-bevelled with piercer (touret)

