



# Seed VMF 3000/H, M, SC

## Automatic 3 hands

Our automatic movement is equipped with a double barrel and a variable inertia balance, giving the movements better operating stability and optimal timing. With its small dimensions rarely found on the market, it offers extremely wide scope for creativity.

<b>Fitting diameter</b>	23.3 mm (10½")
<b>Depth</b>	3.9 mm
<b>Indications and functions</b>	Hour, minute, centre seconds
<b>Type of balance</b>	Variable inertia with gold inertia-blocks
<b>Frequency</b>	4 Hz (28,800 A/h)
<b>Type of stud holder</b>	Mobile
<b>Type of balance-spring</b>	Flat
<b>Type of oscillating weight</b>	Tungsten
<b>Oscillating weight winding direction</b>	Single direction in clockwise sense of the weight viewing from the dial side
<b>Power-reserve</b>	50 hours
<b>Chronometry</b>	Double-barrel rapid rotation in series Variable inertia balance
<b>Number of components</b>	189
<b>Number of jewels</b>	28
<b>Specific features and finishes</b>	<ul style="list-style-type: none"> <li>• Circular-grained plate on dial side and bridge side</li> <li>• Motion-work bridge, circular-grained, dial side</li> <li>• Bridges with Côtes de Genève decor, rhodium-plated, bicolour engraving</li> <li>• Bevels, counterbores and apertures diamond-polished</li> <li>• Ceramic ball-bearing</li> <li>• Pivots and flanges rolled</li> <li>• Wheels circular-grained on 2 faces</li> <li>• Flat-head screws, locked</li> <li>• Bridges hand-bevelled with piercer (touret)</li> </ul>

