



Seed VMF 3002 / H, M, S6H, D

Automatic 3 hands with date

Our automatic movement is equipped with a double barrel and a variable inertia balance, giving the movements better operating stability and optimal timing.

Fitting diameter	25.6 mm (1 1/2")
Depth	3.7 mm
Indications and functions	Hour, minute, seconds sub-dial at 6h, date in a window at 3h or 6h
Type of balance	Variable inertia with gold inertia-blocks
Frequency	4 Hz (28,800 A/h)
Type of stud holder	Mobile
Type of balance-spring	Flat
Type of oscillating weight	Tungsten
Oscillating weight winding direction	Single direction in clockwise sense of the weight viewing from the dial side
Power-reserve	50 hours
Chronometry	Double-barrel rapid rotation in series Variable inertia balance
Number of components	189
Number of jewels	28
Specific features and finishes	<ul style="list-style-type: none"> • Circular-grained plate on dial side and bridge side • Date bridge and motion-work bridge, circular-grained, dial side • Bridges with Côtes de Genève decor, rhodium-plated, bicolour engraving • Bevels, counterbores and apertures diamond-polished • Ceramic ball-bearing • Pivots and flanges rolled • Wheels circular-grained on 2 faces • Flat-head screws, locked • Bridges hand-bevelled with piercer (touret)

